





| PERFORMANCE SPECIFICATION | MIN | TYP | MAX | UNITS |
|---|------|------|------|--------------------|
| Lower Frequency: | | | 2974 | MHz |
| Upper Frequency: | 3274 | | | MHz |
| Tuning Voltage: | 0.3 | | 4.7 | VDC |
| Supply Voltage: | 4.75 | 5.0 | 5.25 | VDC |
| Output Power: | -3.0 | 0 | +3.0 | dBm |
| Supply Current: | | | 27 | mA |
| Harmonic Suppression (2 nd Harmonic) | | -30 | -15 | dBc |
| Pushing: | | 1.5 | 2.5 | MHz/V |
| Pulling, all Phases: | | | 15.0 | MHz pk-pk |
| Tuning Sensitivity: | | 100 | | MHz/V |
| Phase Noise @ 10kHz offset: | | -93 | -90 | dBc/Hz |
| Phase Noise @ 100kHz offset: | | -119 | -116 | dBc/Hz |
| Load Impedance: | | 50 | | Ω |
| Input Capacitance: | | | 30 | pF |
| Operating Temperature Range: | -40 | | +85 | $^{\circ}\text{C}$ |
| Storage Temperature Range: | -45 | | +90 | $^{\circ}\text{C}$ |


FRONT



BACK



SIDE




● Unless otherwise specified, Dimensions are in: $\frac{\text{IN}}{(\text{mm})}$

Product Control:


| | | | |
|----------------------|--------------------|---------------|-------------|
| Crystek Part Number: | CRBV55BE-2974-3274 | Release Date: | 03-Dec-2014 |
| Revision Level: | B | Responsible: | C. Vales |



Phase Noise (1 Hz BW, Typical)



Tuning Curve (Typical)



Product Control:

| | | | |
|----------------------|--------------------|---------------|-------------|
| Crystek Part Number: | CRBV55BE-2974-3274 | Release Date: | 03-Dec-2014 |
| Revision Level: | B | Responsible: | C. Vales |

Specification is subject to change without notice